


CONNECTORS




CON-RXL	Type Connector	Special Features	Maximum Insulation O.D.		PIC-unfilled and PIC-filled	
			Metric (mm)	Inches	AWG	Metric (mm)
		Gel-filled Polypropylene Cat. 5 RUS Listed	2.08	0.082	26-19	0.4-0.9



CON-Y	Type Connector	Special Features	Maximum Insulation O.D.		PIC-unfilled and PIC-filled	
			Metric (mm)	Inches	AWG	Metric (mm)
		Gel-filled Polypropylene Cat. 5 RUS Listed	2.08	0.082	26-19	0.4-0.9



CON-B	Type Connector	Special Features	Maximum Insulation O.D.		PIC-unfilled and PIC-filled	
			Metric (mm)	Inches	AWG	Metric (mm)
		Moisture Resistant Seal, Flame Retardent	3.94	0.155	22-14	0.5-1.5

CRIMP TOOLS



Stepped jaws with a long nose.
For use on conductors less than 19 gauge (0.9mm)
Specifically designed to crimp gel connectors.

CABLE



We stock a variety of cable suitable for the installation of LED modules including:
Internal Cable
Cabochon Cable
Clear Cable
RGB Cable

CABLE CLIPS



Our cable clips are manufactured from soft aluminium on a double-coated polyfoam self adhesive pad which will stick to most clean, dry surfaces.
No special tools are required, simply peel off the backing tape, stick to a suitable surface and bend to the required shape around the cable bundle.
Size 16mm x 10mm. Available in boxes of 250.