

Pre-filled silicone gel connectors for water tight connections.  
Wiring without stripping, for vibration proof and permanent connections



## CON-Y

### 2 WAY IP RATED GEL CONNECTOR - YELLOW CAP

<b>DIMENSIONS:</b>	(W) 10mm x (L) 15mm
<b>CRIMPED HEIGHT</b>	5.8mm
<b>MATERIALS:</b>	POLYPROPYLENE, TIN PLATED BRASS ALLOY, PETROLEUM HYDROCARBON BASE
<b>WIRE RANGE:</b>	19 - 26 AWG
<b>MAX OVERALL DIA. OF CABLE:</b>	2.08mm



## CON-R

### 3 WAY IP RATED GEL CONNECTOR - RED CAP

<b>DIMENSIONS:</b>	(W) 12mm x (L) 18mm
<b>CRIMPED HEIGHT</b>	5.8mm
<b>MATERIALS:</b>	POLYPROPYLENE, TIN PLATED BRASS ALLOY, PETROLEUM HYDROCARBON BASE
<b>WIRE RANGE:</b>	19 - 26 AWG
<b>MAX OVERALL DIA. OF CABLE:</b>	2.08mm



## CON-B

### 3 WAY IP RATED GEL CONNECTOR - BLUE CAP

<b>DIMENSIONS:</b>	(W) 24mm x (L) 24mm
<b>CRIMPED HEIGHT</b>	10mm
<b>MATERIALS:</b>	POLYPROPYLENE, TIN PLATED BRASS ALLOY, PETROLEUM HYDROCARBON BASE
<b>WIRE RANGE:</b>	14 - 22 AWG
<b>MAX OVERALL DIA. OF CABLE:</b>	2.5mm